


COM		
ATIS	127.480	GLOUCESTER INFO
TWR	122.905	GLOUCESTER TOWER
	121.600	GLOUCESTER FIRE
LIGHTING		
APCH 09	HI white basic C/L 30m spacing, with 1 bar.	
APCH 27	HI white intermediate C/L 30m spacing, with 2 bars.	
THR 09/27	Green HI W bars.	
RWY 09/27	Elev HI bi-d 59m spacing, End lights red.	

<b>GUND (Geoid Undulation) =</b> The height of the Geoid (MSL) above the Reference Ellipsoid (WGS 84) at the stated position.	
BEARINGS ARE MAGNETIC	
ELEVATIONS AND HEIGHTS ARE IN FEET	
ELEVATIONS IN FEET AMSL	<b>135</b>
HEIGHTS IN FEET ABOVE AD	<b>(34)</b>



VAR 0.9°W - 2019  
 Annual Rate of Change 0.15°E

RUNWAY/TAXIWAY/APRON PHYSICAL CHARACTERISTICS		
APRON / RWY / TWY	SURFACE	BEARING STRENGTH
RWY 04/22	Asphalt	-
RWY 09/27	Asphalt	16/F/B/Y/U
RWY 18/36	Asphalt	-
RWY 04/22	Grass	-
Main Apron (A)	Asphalt	16/F/B/W/U
Maintenance Apron (B)	Asphalt	-
Tower Apron (C)	Asphalt	-
TWY A	Asphalt	16/F/B/W/U
TWY (All Others)	Asphalt	-

